



Performance Under Pressure.®

Hot Water Pressure Washers

EH Series

HLP Series



EH Series

Electric - Belt Drive - Stationary

If you require the most compact, energy-efficient pressure washer in the industry, then the EH Series is for you. Perfect for in-plant cleaning applications.



Belt drive triplex piston pump with low RPM



Diagnostic control panel for easy operation



All Electric Advantages:

- No refueling
- No ventilation
- No hot exhaust
- No open flame
- No smoke
- No odor

Note: Electrical cord not included.

Additional Features

Pump

- Low pressure chemical injection

Components

- Efficient, on-demand heat exchanger creates continuous hot water
- Adjustable thermostat
- Complete system diagnostic board
- Hour meter
- Fusible plug, temperature sensitive 350°F +/-5%, safety
- Pressure and high limit safety controls

Unit Includes

- 50-foot x 3/8-inch high pressure hose with quick connects
- Single lance with four quick connect nozzles and adjustable soap nozzle

Miscellaneous

- Maintains heat after extended use
- 20-second delay, preset
- Temperature rise 150°F/66°C above ambient
- Low inlet pressure (PSI) shut-off
- Low inlet water volume (GPM) shut-off
- Trigger gun control
- Automatic on/off, controlled at gun



Electric Powered - Belt Drive - Portable

The HLP Series is the perfect solution for jobs that require hot water combined with high pressure. This series is an excellent choice for degreasing, sanitizing and grime removal applications.



HLP-1502-0M10 shown with 10-foot LP gas hose (tank shown is not available through Mi-T-M)



Belt drive triplex piston General pump with ceramic plungers



Tank carrier with snug-fit band for 30-lb. propane tank (tanks sold separately, minimum size is 30-lbs.)



LP-gas shut-off valve



Manual spark ignition

Pump

- Thermal relief valve helps prevent pump damage

Motor

- Open drip-proof electric motor
- 35-foot electrical cord with ground fault circuit interrupter (GFCI) (20-amp plug on 1500-PSI model)

Frame

- Reinforced powder coated cabinet-style steel frame
- Wand holder
- Solid steel axles
- Pneumatic tires with tubes

Components

- LP-gas fired natural draft with aspirating-type burner (vapor-only)
- High limit temperature control for added safety
- Gas regulator

Unit Includes

- Quick connect nozzles (0°, 15°, 25°, 40°) and detergent nozzle
- 50-foot x 3/8-inch steel wire-braided pressure hose with quick connects, swivel and bend restrictors
- Professional-grade insulated trigger gun with safety lock-off
- 36-inch insulated lance

Miscellaneous

- Temperature rise above 150°F above ambient
- Water output temperature in "wet" steam mode is approximately 250°F (700-PSI model)
- Operates at 350-PSI in "wet" steam mode (700-PSI model)
- 200,000-BTU per hour - LP-gas (vapor only)



Mi-T-M offers a full line of products including cold water pressure washers, air compressors, generators, wet/dry vacuums, jobsite boxes, portable heaters and water treatment systems.

EH & HLP Series

Electric Powered - Belt Drive

EH SERIES

Model Number	PSI	GPM	Horsepower	440 Voltage	575 Voltage	Outlet Temperature	Dimensions (LxWxH)	Ship Wt.	Net Wt.
EH-2303-0M30	2300	3.1	5.0 HP	51.0A/36kW	42.0A/36kW	150°F	38in.x21in.x30in.	480 lbs.	430 lbs.
EH-3004-0M30	3000	3.9	7.5 HP	98.0A/72kW	80.0A/72kW	190°F	38in.x21in.x30in.	500 lbs.	450 lbs.

OPTIONS

Part Number	Description	Fits Models
07009	16-foot electrical cord - Adds electrical cord to unit, #4/4 (up to 110 Amps)	EH-3004-0M30
07010	16-foot electrical cord - Adds electrical cord to unit, #8/4 (up to 65 Amps)	EH-2303-0M30
07020	Pump cage - Covers pump with steel cage to protect from moisture and debris	All models
07044	Remote box - Allows unit to be mounted away from wash bay	All models
07109A	Stainless-steel hood - Converts powder coated painted hood to stainless-steel	All models
3104	Portable cart - Converts stationary unit into portable unit	All models
Consult Factory	High pressure chemical injection (includes float tank) - High pressure water mixes with detergent to clean even the heaviest build-up	All models

HLP SERIES

Model Number	PSI	GPM	HP/Motor	Plug Type	BTU Per Hour	Dimensions (LxWxH)	Ship Wt.	Net Wt.
HLP-0703-0M10*	700	2.3	1.5 HP, 120V, 1Ø, 13.2A	NEMA 5-15P	200,000	57.5in.x35.5in.x59.5in.	471 lbs.	348 lbs.
HLP-1502-0M10	1500	1.8	2.0 HP, 120V, 1Ø, 18.8A	NEMA 5-20P	200,000	57.5in.x35.5in.x59.5in.	505 lbs.	382 lbs.

*Combination wet steam cleaner/pressure washer.

OPTION

Part Number	Description	Fits Models
TX-1004-W	Puncture-proof tires - Tires are flat-free, maintenance-free, 10-inch, white hub, four tires	All models

NEMA 5-15P,
15-amp plugNEMA 5-20P,
20-amp plug

Mi-T-M Corporation
8650 Enterprise Drive
Peosta, IA 52068
800-553-9053
563-556-1235 fax
corp@mitm.com
www.mitm.com

Distributed by: