

13,000 & 14,000-Watt Gasoline

Designed for the contractor, this generator is built to withstand even the most demanding applications. With a reputation for performance it is a virtual powerhouse with the added benefit of being portable enough to easily move from jobsite to jobsite.

**New
14,000-Watt
Model**

Engine

- Low-oil shutdown engine with electric start (battery included)
- Idle control

Alternator

- Brushless 120V/240V alternator
- Total harmonic distortion (THD) less than 5%
- 100% copper windings

Frame

- Reinforced 1¼-inch powder coated steel tube frame with center balanced lifting hook
- Solid steel threaded axles
- Four pneumatic tires with tubes and locking tire brake

Components

- Large low-tone mufflers to reduce noise to lowest level possible
- Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles
- Easy-to-read fuel gauge
- Voltmeter/hour meter
- Fuel tanks are powder coated outside, zinc-plated inside to prevent rusting
- Heavy-duty industrial air cleaners hold up under extreme conditions

Miscellaneous

- USDA/USFS-approved spark arrestors
- Circuit breaker protected

Warranties

2 YEAR LIMITED ALTERNATOR WARRANTY
3 YEAR LIMITED HONDA ENGINE WARRANTY
3 YEAR LIMITED SUBARU ENGINE WARRANTY



GEN-14000-1MHE

Model Number	GEN-13000-1MSE*	GEN-14000-1MHE^
Max. AC Output	13,000 watts	14,000 watts
Rated AC Output	11,500 watts	12,000 watts
Displacement/Engine	650cc Subaru OHV	688cc Honda OHV
Frequency/Voltage	60Hz/120V/240V	60Hz/120V/240V
Max. Amps (120V/240V)	108.3/54.2	116.7/58.3
Cont. Amps (120V/240V)	95.8/47.9	100.0/50.0
Receptacles	(2) 120V, 20A GFCI duplex 120V, 30A twist lock 120V/240V, 30A twist lock 120V/240V, 50A	(2) 120V, 20A GFCI duplex 120V, 30A twist lock 120V/240V, 30A twist lock 120V/240V, 50A
Main Circuit Breakers	(2) 20A toggle circuit breaker, single pole 30A toggle circuit breaker, single pole 30A toggle circuit breaker, double pole 50A toggle circuit breaker, double pole	(2) 20A toggle circuit breaker, single pole 30A toggle circuit breaker, single pole 30A toggle circuit breaker, double pole 50A toggle circuit breaker, double pole
Rated Speed	3600 RPM	3600 RPM
Decibel Rating	77.5	77.5
Fuel Capacity	13.2 gallons	13.2 gallons
Run Time (at full load)	8.8 hours	8.0 hours
Dimensions (LxWxH)	31.5in.x30.5in.x37.5in.	31.5in.x30.5in.x37.5in.
Ship Wt.	573 lbs.	568 lbs.
Net Wt.	513 lbs.	508 lbs.

Noise level tested at seven meters (75% load). Rating represents minimum noise level rating.
 *EPA compliant in 49 states. Not to be sold in California. ^Carb compliant in all 50 states. Can be sold in California.

ACCESSORIES & OPTIONS

Part Number	Description	Fits Models
32-0915	RV generator adapter - 30A/125V female/male; use to connect RV cordsets to 30A generators	All models
GX-0003	Skid feet - For stationary applications	All models
GX-0005	50-amp twist lock receptacle - Marine receptacle for routine marine applications	All models
TX-1304-W	Puncture-proof tires - Tires are flat-free and maintenance-free, 13-inch, white hub, four tires	All models