

# **Work Pro<sup>®</sup> Series**

Cold Water Pressure Washers



Designed with a powder coated steel frame and flat-free tires, the Work Pro Series is portable and easy to move from one job to the next.

## PUMP

- Equipped with Mi-T-M Pressure Relief Start
- Brass manifold
- Thermal relief valve
- In-line water strainer
- Built-in low pressure detergent injector

# FRAME

- Powder coated steel frame
- 10-inch flat-free tires

#### UNIT INCLUDES

- Quick connect nozzles 15°, 25° and detergent nozzle
- 25-foot x %-inch wire-braided high pressure hose (50-foot on WP-3600 and WP-4200 models)
- Two-piece, 36-inch lance
- Professional-grade trigger gun

### LIMITED WARRANTIES

- 1 year pump
- 3 year engine



# Work Pro<sup>®</sup> Series Cold Water – Gasoline – Direct Drive

| USAGE               | COMMERCIAL            | COMMERCIAL             | COMMERCIAL             | COMMERCIAL             | COMMERCIAL             | COMMERCIAL             |
|---------------------|-----------------------|------------------------|------------------------|------------------------|------------------------|------------------------|
| MODEL NUMBER        | WP-3200-0MHB          | WP-3200-0MKB           | WP-3600-0MHB           | WP-3600-0MKB           | WP-4200-0MHB           | WP-4200-0MKB           |
| PSI                 | 3200                  | 3200                   | 3600                   | 3600                   | 4200                   | 4200                   |
| GPM                 | 2.4                   | 2.4                    | 2.8                    | 2.8                    | 3.4                    | 3.4                    |
| DISPLACEMENT/ENGINE | 196cc Honda GX200 OHV | 208cc Kohler CH270 OHV | 270cc Honda GX270 OHV+ | 277cc Kohler CH395 OHV | 389cc Honda GX390 OHV+ | 429cc Kohler CH440 OHV |
| PUMP                | Mi-T-M, crankshaft    | Mi-T-M, crankshaft     | AR, crankshaft         | AR, crankshaft         | Mi-T-M, crankshaft     | Mi-T-M, crankshaft     |
| UNLOADER            | Adjustable pressure   | Adjustable pressure    | Adjustable pressure    | Adjustable pressure    | Adjustable pressure    | Adjustable pressure    |
| DIMENSIONS (LxWxH)  | 37x21x24.5in.         | 37x21x24.5in.          | 40x22.5x24.5in.        | 40x22.5x24.5in.        | 40x22.5x24.5in.        | 40x22.5x24.5in.        |
| SHIP WT.            | 110 lb.               | 110 lb.                | 180 lb.                | 180 lb.                | 192 lb.                | 192 lb.                |
| NET WT.             | 85 lb.                | 85 lb.                 | 130 lb.                | 130 lb.                | 142 lb.                | 142 lb.                |

Note: All gasoline models sold in California are required to have a CARB compliant engine. Consult factory. +49 state engine. Not for sale in California.

#### ACCESSORIES:

| PART NUMBER D | ESCRIPTION |
|---------------|------------|

| PART NUMBER  | DESCRIPTION  | FITS MODELS    |
|--------------|--|----------------|
| 15-0270      | 50-foot hose x %-inch wire-braided hose – Hose upgrade   | All models     |
| 15-0277      | 25-foot hose x 3%-inch wire-braided hose – Hose upgrade  | WP-3200 models |
| AW-7310-0003 | Rotating nozzle – Increase your cleaning power and decrease your cleaning time, 0° spray with 25° coverage, 3.0 orifice size | WP-3200 models |
| AW-7510-0003 | Rotating nozzle – Increase your cleaning power and decrease your cleaning time, 0° spray with 25° coverage, 3.0 orifice size | WP-3600 models |
| AW-7510-0035 | Rotating nozzle – Increase your cleaning power and decrease your cleaning time, 0° spray with 25° coverage, 3.5 orifice size | WP-4200 models |

#### OPTIONS:

| PART NUMBER | DESCRIPTION  | FITS MODELS    |
|-------------|--|----------------|
| CX-0080*    | 50-foot hose x %-inch wire-braided hose – Hose upgrade | WP-3200 models |
| 4           |  |                |

\*This hose replaces the standard hose that is included with the unit.



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.